

6TH AVE N/BENCH –BLGS Phase II




Study Objectives

- Evaluate existing and future traffic conditions on Main Street between Airport Road and 1st Avenue
- Determine what, if any design improvements should be considered for intersection of Main Street with:
 - Bench Blvd/6th Avenue
 - 1st Ave/US 87
- Determine what, if any MetraPark events should utilize a 'release plan'

Study area intersections

- Airport Rd
- 6th Ave/Bench Blvd
- 4th Ave
- 1st Ave/US 87



Study Baseline Assumptions

- 1. Billings Bypass will be operational by 2020**
2. Inner Belt Loop operational before 2033.
3. Use existing coordinated signal timing

Data Collection

- April 2012 and again in July 2012 .
- Past traffic reports and documentation associated with the *6th Avenue North to Bench Boulevard* project.
- Field reconnaissance and observation.
- Parking information for MetraPark.

Site Observations


- Un-serviced demand at intersections due to congestion
- Heavy truck convoys cause lane blockage and spillback
- Lane choices and weaving can be challenging
- 1st Ave/US 87 intersection back up
- Very few pedestrians, except during Metra events
- Metrapark underutilizes the Main Street – Bench intersection

Traffic Projections


Projected existing traffic for **2020 and 2033 with and without bypass in-place**




EXISTING (2012) TRAFFIC



2033 TRAFFIC W/ BYPASS



2033 TRAFFIC W/OUT BYPASS



Projections Summary

- In 20 years, Main Street- 4th Ave to Airport Rd
 - Increase approx . 15-20% with bypass
 - Increase approx. **40-45% without bypass**
- In 20 years, Main Street- 1st Ave to 4th Ave ADT
 - increase approx 4% (1,300 vpd) with the bypass
 - increase approx **40% (13,500 vpd) without bypass**
- In 20 years, Bench Blvd (along MetraPark)
 - Increase approx. 40% with bypass
 - Increase approx. **65% without bypass**
- In 20 years, right-turn PM peak hr volume from US87 onto Main Street
 - decreases from 836 vph (existing) to 256 vph with the bypass
 - increases from 836 vph to **1200 vph without bypass.**

EXISTING LEVEL OF SERVICE (LOS)

| Intersection | Existing (2012) | | | | | |
|-----------------------------------|----------------------|-----|-----------------------|----------------------|-----|-----------------------|
| | AM Peak | | | PM Peak | | |
| | Avg Delay (s/veh) | LOS | Max Queue (veh) | Avg Delay (s/veh) | LOS | Max Queue (veh) |
| | | | | | | |
| Main St & Airport Rd | 43.1 | D | 58 | 40.2 | D | 30 |
| | | | | | | |
| Main St & Bench Blvd/6th Ave N | 17.1 | B | 18 | 8.5 | A | 42 |
| | | | | | | |
| Main St & 4th Ave N | 11.1 | B | 8 | 200.0 | F | 44 |
| | | | | | | |
| Main St & 1st Ave N/Hwy 87 | 25.9 | C | 25 | 30.6 | C | 25? |

2033 LEVEL OF SERVICE

| Intersection | Approach | Design Year (2033) without Bypass | | | | | | Design Year (2033) with Bypass | | | | | |
|---|--------------|-----------------------------------|-----|-----------------------|-------------------------|-----|-----------------------|--------------------------------|-----|-----------------------|-------------------------|-----|-----------------------|
| | | AM Peak | | | PM Peak | | | AM Peak | | | PM Peak | | |
| | | Avg Delay (s/veh) | LOS | Max Queue (veh) | Avg Delay (s/veh) | LOS | Max Queue (veh) | Avg Delay (s/veh) | LOS | Max Queue (veh) | Avg Delay (s/veh) | LOS | Max Queue (veh) |
| Intersection Control | | Existing Traffic Signal | | | | | | Existing Traffic Signal | | | | | |
| Main Street & Airport Road | Intersection | 200.2 | F | 97 | 88.2 | F | 54 | 142.3 | F | 79 | 75.9 | E | 47 |
| Intersection Control | | Existing Traffic Signal | | | | | | Existing Traffic Signal | | | | | |
| Main Street & Bench Blvd/ 6th Avenue N | Intersection | 75.1 | E | 36 | 76.9 | E | 68 | 32.8 | C | 30 | 27.0 | C | 54 |
| Intersection Control | | Existing Traffic Signal | | | | | | Existing Traffic Signal | | | | | |
| Main Street & 4th Avenue N | Intersection | 22.3 | C | 15 | 282.2 | F | 74 | 14.8 | B | 10 | 239.2 | F | 74 |
| Intersection Control | | Existing Traffic Signal | | | | | | Existing Traffic Signal | | | | | |
| Main Street & 1st Avenue N/Hwy 87 | Intersection | 34.2 | C | 36 | 45.3 | D | 29? | 32.8 | C | 39 | 43.4 | D | 29? |

6th Avenue/Bench Blvd – Main Intersection





ALTERNATIVES:

1. **No-build** – this option would perpetuate existing conditions.
2. **Roundabout** –construct a multilane roundabout
3. **Combine 4th Avenue and 6th Avenue** –join 4th Avenue to 6th Avenue and Bench Blvd.
4. **Signalized Intersection Improved** – construct improvements to the existing intersection
5. **Overpass** – extend Bench Blvd over Main Street with or without ramps onto 6th Ave and Main St
6. **Underpass** - underpass w/ 1-lane off-ramp to Main & 1-lane off-ramp to Bench
7. **4th Avenue Flyover** – connect 4th Avenue to Main Street via a flyover. and 4th Ave to Bench Blvd via a one-lane structure


1. No-Build



| 23:10:12 | | MAIN+6TH+BENCH 2033 | | | | | | | | 152 | |
|--|------|---------------------|--------------------------|-------|-------|----------------|------------|----|------|-----------|---------------|
| E | <m> | 11.00 | 5.4 | 11.0 | 11.0 | TIME PERIOD | | | | min | 90 |
| L' | <m> | 30.0 | 30.0 | 30.00 | 30.0 | TIME SLICE | | | | min | 15 |
| U | <m> | 10.00 | 4.20 | 10.00 | 10.00 | RESULTS PERIOD | | | | min | 15 75 |
| RAD | <m> | 25.00 | 25.00 | 25.00 | 25.00 | TIME COST | | | | \$/hr | 15.00 |
| PHI | <d> | 20.00 | 20.00 | 20.00 | 20.00 | FLOW PERIOD | | | | min | 15 75 |
| DIA | <m> | 54.00 | 64.00 | 54.00 | 64.00 | FLOW TYPE | | | | pcu/veh | VEH |
| GRAD SEP | | 0 | 0 | 0 | 0 | FLOW PEAK | | | | am/op/pm | AM |
| | | | | | | | | | | | |
| LEG NAME | PCU | VEH | TURNS <1st exit, 2nd..U> | | FLOF | CL | FLOW RATIO | | | FLOW TIME | |
| NORTH | 1.02 | | 0 | 1621 | 0 | 0 | 1.00 | 50 | 0.75 | 1.125 | 0.75 15 45 75 |
| WEST | 1.02 | | 0 | 0 | 0 | 0 | 1.00 | 50 | 0.75 | 1.125 | 0.75 15 45 75 |
| SOUTH | 1.02 | | 0 | 968 | 248 | 0 | 1.00 | 50 | 0.75 | 1.125 | 0.75 15 45 75 |
| EAST | 1.02 | | 0 | 661 | 525 | 0 | 1.00 | 50 | 0.75 | 1.125 | 0.75 15 45 75 |
| | | | | | | | | | | | |
| MODE 2 | | | | | | | | | | | |
| FLOW | veh | | 1621 | 0 | 1216 | 1186 | | | | AUEDEL | s 14.7 |
| CAPACITY | veh | | 2060 | 474 | 3383 | 2365 | | | | LOS | SIG B |
| AUE DELAY | mins | | 0.35 | 0.13 | 0.16 | 0.18 | | | | LOS | UNSIG B |
| MAX DELAY | mins | | 0.57 | 0.13 | 0.17 | 0.21 | | | | | |
| AUE QUEUE | veh | | 6 | 0 | 1 | 1 | | | | VEHIC | HRS 16.5 |
| MAX QUEUE | veh | | 11 | 0 | 1 | 1 | | | | COST | \$ 247 |
| F1mode F2direct F3peak CtrlF3rev F4fact F6stats F8econ F9prnt F10run Esc | | | | | | | | | | | |

| 23:10:12 | | MAIN+6TH+BENCH 2033 | | | | | | | | 151 | |
|--|------|---------------------|--------------------------|-------|-------|----------------|------------|----|------|-----------|---------------|
| E | <m> | 11.00 | 5.4 | 11.0 | 11.0 | TIME PERIOD | | | | min | 90 |
| L' | <m> | 30.0 | 30.0 | 30.00 | 30.0 | TIME SLICE | | | | min | 15 |
| U | <m> | 10.00 | 4.20 | 10.00 | 10.00 | RESULTS PERIOD | | | | min | 15 75 |
| RAD | <m> | 25.00 | 25.00 | 25.00 | 25.00 | TIME COST | | | | \$/hr | 15.00 |
| PHI | <d> | 20.00 | 20.00 | 20.00 | 20.00 | FLOW PERIOD | | | | min | 15 75 |
| DIA | <m> | 54.00 | 64.00 | 54.00 | 64.00 | FLOW TYPE | | | | pcu/veh | VEH |
| GRAD SEP | | 0 | 0 | 0 | 0 | FLOW PEAK | | | | am/op/pm | PM |
| | | | | | | | | | | | |
| LEG NAME | PCU | VEH | TURNS <1st exit, 2nd..U> | | FLOF | CL | FLOW RATIO | | | FLOW TIME | |
| NORTH | 1.02 | | 0 | 1083 | 0 | 0 | 1.00 | 85 | 0.75 | 1.125 | 0.75 15 45 75 |
| WEST | 1.02 | | 0 | 0 | 0 | 0 | 1.00 | 85 | 0.75 | 1.125 | 0.75 15 45 75 |
| SOUTH | 1.02 | | 0 | 3410 | 47 | 0 | 1.00 | 85 | 0.75 | 1.125 | 0.75 15 45 75 |
| EAST | 1.02 | | 0 | 178 | 220 | 0 | 1.00 | 85 | 0.75 | 1.125 | 0.75 15 45 75 |
| | | | | | | | | | | | |
| MODE 2 | | | | | | | | | | | |
| FLOW | veh | | 1083 | 0 | 3457 | 398 | | | | AUEDEL | s 137.0 |
| CAPACITY | veh | | 2775 | 727 | 3180 | 548 | | | | LOS | SIG F |
| AUE DELAY | mins | | 0.17 | 0.13 | 3.14 | 0.58 | | | | LOS | UNSIG F |
| MAX DELAY | mins | | 0.18 | 0.13 | 6.46 | 0.92 | | | | | |
| AUE QUEUE | veh | | 1 | 0 | 213 | 3 | | | | VEHIC | HRS 187.9 |
| MAX QUEUE | veh | | 1 | 0 | 334 | 5 | | | | COST | \$ 2819 |
| F1mode F2direct F3peak CtrlF3rev F4fact F6stats F8econ F9prnt F10run Esc | | | | | | | | | | | |


3. Combine 4th and 6th Avenue (at-grade)




4th and 6th Avenue (at-grade) snapshot




4. Signalized Intersection Improved




5. Overpass (by others)



6. Underpass (by others)



Overpass and Underpass




Concerns with Under/Overpass

- Weaving to make left-turn at US87
- Utilities – underpass and oil line
- Costs – structures are expensive
- Traffic Impacts during construction

Rendering of Bridge



7. 4th Avenue Flyover





Decision Matrix

6th Ave/Bench Blvd-Main Street

| Criteria - Construction Impacts | Do- Nothing | Modify Existing Signal | Roundabout | Underpass | Overpass | 4 th Ave Flyover | Combine 4 th and 6 th |
|---------------------------------------|----------------|------------------------------|------------|-----------|----------|--------------------------------|--|
| Mobility | + | - | - | - | + | - | - |
| Utilities | + | + | - | - | + | + | - |
| Right of Way | + | + | - | - | - | - | - |
| Socio Economic | + | + | - | - | - | - | - |
| Environmental | + | + | + | + | + | + | - |
| Pedestrians | + | + | - | + | + | - | - |
| MetraPark | + | + | - | - | + | + | - |
| Transit | + | + | - | - | + | + | + |
| Emergency Services | + | + | - | - | + | + | + |

Decision Matrix

6th Ave/Bench Blvd-Main Street

| Criteria – Environmental | Do- Nothing | Modify Existing Signal | Rdbt | Underpass | Overpass | 4 th Ave Flyover | Combine 4 th and 6 th |
|-----------------------------|----------------|------------------------------|---------------|------------|----------|--------------------------------|--|
| Viewshed | + | + | + | + | - | - | + |
| Displacement of property | + | + | - | - | - | - | - |
| Natural Resources | + | + | - | - | - | - | - |
| Noise | - | - | - | - | - | + | - |
| Business | - | - | - | + | + | + | - |
| Primary Concern | congestion | congestion | Land Req't | Land Req't | View | View | Land Req't |

Decision Matrix

6th Ave/Bench Blvd-Main Street

| Criteria – Transportation System | Do- Nothing | Modify Existing Signal | Rdbt | Underpass | Overpass | 4 th Ave Flyover | Combine 4 th & 6 th |
|--|----------------|------------------------------|----------|--------------------|--------------------|--------------------------------|--|
| Level of Service | C | C | F | A* | A* | B | F |
| Motorist Delay | - | - | - | + | + | + | - |
| Mobility | - | - | + | + | + | + | - |
| Safety | - | + | + | + | + | + | - |
| Traffic Patterns | + | + | - | - | - | + | + |
| Future Capacity | - | - | - | + | + | + | - |
| Emissions | - | - | + | + | + | + | - |
| Pedestrians | - | - | - | + | + | - | - |
| Local Planning | - | - | - | + | + | + | - |
| MetraPark | - | - | - | + | + | - | - |
| Primary Concern | Capacity | Cost vs Benefit | Capacity | Weaving on Main | Weaving on Main | Structure placement | Capacity |

* don't forget about 4th Ave; it will remain congested


Costs

| Criteria – Costs | Do-Nothing | Modify Existing Signal | Rdbt | Underpass | Overpass | 4 th Ave Flyover | Combine 4 th and 6 th |
|-------------------------------------|------------|------------------------|------|-----------|----------|-----------------------------|---|
| Construction – CN +CE | + | + | - | - | - | - | - |
| Utilities | + | + | - | - | - | - | - |
| Right-of-Way (\$15/ft) | + | + | - | - | - | - | - |
| Traffic Control | + | + | - | - | - | - | - |
| Fuel Consumption per year (no infl) | - | - | + | + | + | + | - |
| Economic | - | - | - | + | + | + | - |
| O & M | - | - | + | + | + | + | - |


1st Avenue/Main/US 87 Intersection



Right-turn slip lane



Dual Right-turn lane



Roundabout




1st Avenue/Main/US 87 Intersection - LOS Results

| Intersection | Existing (2012) | | | | | | Design Year (2033) with Bypass | | | | | |
|--------------------------------------|--------------------------------|-----|--------------------|----------------------|-----|--------------------|--|-----|--------------------|----------------------|-----|--------------------|
| | AM Peak | | | PM Peak | | | AM Peak | | | PM Peak | | |
| | Avg Delay (s/veh) | LOS | Max Queue (veh) | Avg Delay (s/veh) | LOS | Max Queue (veh) | Avg Delay (s/veh) | LOS | Max Queue (veh) | Avg Delay (s/veh) | LOS | Max Queue (veh) |
| | <i>Existing Traffic Signal</i> | | | | | | <i>Existing Traffic Signal</i> | | | | | |
| Main Street & 1st Avenue N/Hwy 87 | 25.9 | C | 25 | 30.6 | C | 18 | 32.8 | C | 39 | 43.4 | D | 29 |
| | | | | | | | <i>Option 1: Elim outside NB Thru/ Add WB free right</i> | | | | | |
| | | | | | | | 33.3 | C | 39 | 60.6 | E | 52 |
| | | | | | | | <i>Option 2: Add WB dual right</i> | | | | | |
| | | | | | | | 31.0 | C | 39 | 73.5 | E | 29 |
| | | | | | | | <i>Option 3: Roundabout</i> | | | | | |
| | | | | | | | 10.6 | B | 1 | 15.0 | C | 6 |

MetraPark

When is 'release plan'
needed?



MetraPark Release Plan - Assumptions

- Event is coincident with average PM peak hour
- 2.5 occupants/vehicle
- Release occurs over a 1-hour period
- 50% of release traffic will enter through Bench/6th Ave/Main intersection for SB travel on Main or WB travel on 6th Ave
- Seating capacity of arena is 12,000 people, including 10,000 in regular seating and another 2,000 available floor seating

MetraPark Release Plan - Results

Release plan is required when an event yields 6000 (50% total capacity of arena) attendees and the event has a distinct 'end'.

CONCLUSIONS

1. Main Street operates pretty well the majority of the time.
2. Traffic will increase slightly until 2020 (Billings Bypass is operational).
3. When bypass opens, traffic will drop very quickly on Main Street and US 87.
4. After initial drop, traffic will gradually increase so by 2033 they are nearly the same as 2020 levels before bypass opened.
5. Although 2033 conditions are likely to produce more delay and queue potential of vehicles, the intersections appear to operate within acceptable LOS.
6. The 6th Ave/Bench and 1st Ave/US 87 intersections will continue to operate well, with congestion similar to existing conditions through year 2033.
7. The addition of another lane to Main Street demonstrates very little benefit.
8. The intersection of Airport Road and Main Street appears most likely to become saturated.
9. The Flyover concept at 6th/Bench-Main has a significant amount of merit for a future project, particularly from an emissions standpoint.
10. A noise analysis is likely justified with any major improvements.
11. Development per BIRD and EBURD could significantly change traffic conditions. Suggest reassessing after development plans are better known (2013)

Recommendation

Main St/Bench Blvd-Main St. intersection

- Option 1 – DO NOTHING (reassess options after Bypass is open)
- Option 2 – Flyover (long term-bang for the buck)

1st Ave/US 87 – Main St intersection

- Option 1 – DO NOTHING
- Option 2 – Right-turn slip lane (interim until 2020)