

Invitation for Bid: Level IIIA Ballistic Shields

Addendum I

14 Apr 2021

We've received several requests for clarifications concerning our IFB for Ballistic Shields minimum performance requirements. PLEASE ADD TO MINIMUM REQUIREMENTS:

What is the minimum size for the shield?	No less than 18" wide and no larger than 30" in height
What is the desired weight of the shield?	Should not exceed 15lbs
What is the minimum lumens required for the light...strobe or no strobe function	Minimum of 500 lumens with an ambidextrous light switch mounted fully integrated in the weak hand handle (STROBE IS NOT desired)
Do you have any minimum size for the viewport	No smaller than 2.75" high and 8"-15" wide
Specific shape? IE Rectangle or would you like the shield to have "cut outs" on the top for officers to be able to deploy their service pistols while holding the shield?	Oblong, rectangular, or similar shapes with or without cut-outs for handgun deployment
Are there any minimum warranty/liability requirements...Berry compliant or Made in the USA	Warranties for manufacturing processes and materials for a minimum of 5 years, and liability of no less than \$1,500,000 as a minimum. Made in USA
Any type of specific finish?	Painted or otherwise covered in dark non-reflective coating
Minimum standards for certifications?	Meet Federal Standard NIJ-STD 0108.01 certification/testing level